SHERWIN INCORPORATED

DUBL CHEK

CERTIFICATION

June 4, 2025

Product: HM-3A

Batch No.: 510-E73

Type: I Methods: A and C

Sensitivity Level: 2

It is hereby certified that this material has been manufactured in accordance with, and conforms to, AMS 2644J. Results of the required quality conformance tests, as stipulated by paragraph 4.3.2, are listed below.

Test Method Paragraph	Test Description	Results
3.3.3	Flash point i.a.w. ASTM D93	>230°F
3.3.4	Viscosity i.a.w. ASTM D445 at 100 ± 1°F	7.33 cSts
3.3.8.3.3	Fluorescent brightness i.a.w. ASTM E1135 (Type I only)	85.3 %
3.3.8.5	Water tolerance	12.3 %
3.3.8.7	Removability	Conforms
3.3.8.8	Water Content	0.29%
---	Chloride content i.a.w. ASTM E165, Annex 4	<0.0002% BW
---	Sulfur content i.a.w. ASTM E165, Annex 4	<0.0001% BW
---	Fluoride content i.a.w. ASTM E165, Annex 4	<0.0001% BW

It is further certified that this material is listed or approved for listing on QPL-AMS-2644. The material was analyzed in accordance with and meets the detection limits for fluoride, chloride, and sulfur per ASME Boiler and Pressure Vessel Code, Section V, Article 6, paragraph T-641, 1998 - 2023 Editions and addenda. It also meets the requirements of ASTM E1417.

SHERWIN INCORPORATED

Q.C. Laboratory

Corporate
5530 Borwick Avenue I South Gate, CA 90280
P: (562) 861-6324 I **F:** (562) 923-8370
sherwin@sherwininc.com

Midwest
1615 Distribution Drive I Burlington, KY 41005
P: (859) 525-6881 I **F:** (859) 525-6887
sherwin.ky@sherwininc.com