

CERTIFICATION

August 25, 2025

Product: DR-64

Batch No.: 514-HS18

Class: 2

It is hereby certified that this material has been manufactured in accordance with, and conforms to, AMS 2644J. Results of the required quality conformance tests, as stipulated by paragraph 4.3.2, are listed below.

<u>Test Method Paragraph</u>	<u>Test Description</u>	<u>Results</u>
3.3.11	Fluorescence	Conforms
---	Residue i.a.w. ASME B&PV Code, Section 5, Article 6, para T-641	<u><0.0001% BW</u>

It is further certified that this material is listed or approved for listing on QPL-AMS-2644.. It also meets the requirements of ASTM E1417.

SHERWIN INCORPORATED



Q.C. Laboratory

Note regarding cleaner/remover: In accordance with specifications and code procedures, prior to the ASTM E165, Annex A4 test a 100 gram sample is evaporated at elevated temperatures. If, after evaporation, the residue is 0.005 grams (50 ppm) (0.0050%) or less, fluoride, chloride, and sulfur analyses are not performed, and the weight of the residue is reported instead.

Corporate
5530 Borwick Avenue | South Gate, CA 90280
P: (562) 861-6324 | **F:** (562) 923-8370
sherwin@sherwininc.com

Midwest
1615 Distribution Drive | Burlington, KY 41005
P: (859) 525-6881 | **F:** (859) 525-6887
sherwin.ky@sherwininc.com