

**CERTIFICATION**

March 11, 2025

Product: WB-200C

Batch No.: 59-CS16

Type: 1 Methods: A and C

Sensitivity Level: 2

It is hereby certified that this material has been manufactured in accordance with, and conforms to, AMS 2644J. Results of the required quality conformance tests, as stipulated by paragraph 4.3.2, are listed below.

Test Method Paragraph	Test Description	Results
3.3.3	Flash point i.a.w. ASTM D93*	>200°F
3.3.4	Viscosity i.a.w. ASTM D445 at 100 ± 1°F*	21.33 cSts
3.3.8.3.3	Fluorescent brightness i.a.w. ASTM E1135 (Type I only)*	92.7%
3.3.8.5	Water tolerance	N/A
3.3.8.6	Removability*	Conforms
3.3.8.7	Water Content	51.47%
---	Chloride content i.a.w. ASTM E165, Annex 4	<0.0001% BW
---	Sulfur content i.a.w. ASTM E165, Annex 4	<0.0006% BW
---	Fluoride content i.a.w. ASTM E165, Annex 4	<0.0001% BW

\* These tests were run on a concentration of 50% in water

It is further certified that this material is listed or approved for listing on QPL-AMS-2644. The material was analyzed in accordance with and meets the detection limits for fluoride, chloride, and sulfur per ASME Boiler and Pressure Vessel Code, Section V, Article 6, paragraph T-641, 1998 - 2023 Editions and addenda.

**SHERWIN INCORPORATED**



**Q.C. Laboratory**

**Corporate**  
 5530 Borwick Avenue | South Gate, CA 90280  
 P: (562) 861-6324 | F: (562) 923-8370  
 sherwin@sherwininc.com

**Midwest**  
 1615 Distribution Drive | Burlington, KY 41005  
 P: (859) 525-6881 | F: (859) 525-6887  
 sherwin.ky@sherwininc.com