www.sherwininc.com • email: sherwin@sherwininc.com

October 22, 2015

## **CERTIFICATION**

We hereby certify that samples of the material identified below by batch number, have been analyzed in accordance with test methods that meet and/or exceed the detection limits for fluoride, chloride, and sulfur per ASM Boiler and Pressure Vessel Code, Section V, Article 6, paragraph T-641, 1998 - 2013 Editions and addenda, with the following results:

<b>FLUORIDE</b>	<b>CHLORIDE</b>	<b>SULFUR</b>
<b>ASTM E165</b>	<b>ASTM E165</b>	<b>ASTM E165</b>
ANNEX A4	ANNEX A4	ANNEX A4

DUBL-CHEK DP-51 <0.0002%BW <0.0044%BW <0.0027%BW

**BATCH NO.** 511-J47

We further certify that this material meets or exceeds the requirements of AMS 2644, MIL-I-25135, Revision E and ASTM E1417.

Copies of the certification and laboratory reports are on file in our office for your inspection.

SHERWIN INCORPORATED

George Murphy QC Chemist

Revision: August 2001

www.sherwininc.com • email: sherwin@sherwininc.com

## **CERTIFICATE OF CONFORMANCE**

Date: October 22, 2015

Product: DP-51

Batch No.: 511-J47

Type: II Methods: A and C

It is hereby certified that this material has been tested in accordance with AMS 2644. Results of the required quality conformance tests, as stipulated by paragraph 4.3.2, are listed below.

Test Method Paragraph	Test Description	Results
3.3.3	Flash point i.a.w. ASTM D93	>230°F
3.3.4	Viscosity i.a.w. ASTM D445 at 100 ± 1°F	5.22 cStS
3.3.8.5	Water tolerance (Method A only)	23.1 %
3.3.8.6	Removability	Conforms
	Fluoride content i.a.w. ASTM E165, Annex 4	<0.0002%BW
	Chloride content i.a.w. ASTM E165, Annex 4	<0.0044%BW
	Sulfur content i.a.w. ASTM E165, Annex 4	<0.0027%BW

It is further certified that this material is listed or approved for listing on QPL-AMS-2644. It also meets the requirements of MIL-I-25135E, ASTM E1417, and MIL-STD-6866.

SHERWIN INCORPORATED

George Murphy QC Chemist

Revision: January 2000