

DR-60 Remover Spray Can

1 PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: DR-60 Remover Spray Can
SDS Number: DR-60-SC
Revision Date: 6/14/2022
Product Use: NDT Inspection Remover

Supplier Details: Sherwin Inc.
5530 Borwick Avenue
South Gate, CA 90280

Phone: 562-861-6324
Email: sherwin@sherwininc.com
Internet: www.sherwininc.com

Emergency telephone number:

ChemTel 1-800-255-3924 in U.S.A, Canada, Puerto Rico and US Virgin Islands;
ChemTel +1-813-248-0585 outside U.S.A, Canada, Puerto Rico and US Virgin Islands
ChemTel Brazil: 0-800-591-6042, China: 400-120-0751, India: 000-800-100-4086 and Mexico: 01-800-099-0731

2 HAZARDS IDENTIFICATION

Classification of Substance

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Physical, Flammable Aerosols, 1
Health, Aspiration hazard, 1

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: **DANGER**

GHS Hazard Pictograms:



GHS Hazard Statements:

H222 - Extremely flammable aerosol
H304 - May be fatal if swallowed and enters airways
H229 - Pressurized container: may burst if heated

GHS Precautionary Statements:

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P242 - Use non-sparking tools.
P243 - Take action to prevent static discharges.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash ... thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P281 - Use personal protective equipment as required.
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P311 - IF exposed or concerned: Call a POISON CENTER/doctor/...
P370 + P378 - In case of fire: Use dry chemical, alcohol resistant foam or dry sand to extinguish.
P403 + P235 - Store in a well-ventilated place. Keep cool.
P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.



DR-60 Remover Spray Can

3 COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Ingredients:		
CAS#	%	Chemical Name:
68476-86-8	20-30%	Propane/ Isobutane
64742-48-9	70-80%	Naphtha (petroleum), hydrotreated heavy

4 FIRST AID MEASURES

- Inhalation:** Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.
- Skin Contact:** Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor
- Eye Contact:** Immediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids to facilitate irrigation. Get immediate medical attention.
- Ingestion:** Clean mouth with water. Keep respiratory tract clear.
Do NOT induce vomiting or attempt chemical neutralization. If symptoms persist, call a physician.

5 FIRE FIGHTING MEASURES

- Flash Point:** 45°C (113 °F) liquid
- Flash Point Method:** ASTM D-56
- Autoignition Temp:** 345°C liquid
- Lower Explosive Limit:** 0.7%(V) isoalkanes
- UEL:** 6%(V) isoalkanes
- Suitable extinguishing agents:** Alcohol resistant foam, dry chemical, carbon dioxide

Special hazards arising from the substance or mixture: Spray can under pressure. Carbon monoxide and carbon dioxide

Protective equipment: Wear self-contained respiratory protective device. Wear fully protective suit

Unsuitable extinguishing media: High volume water jet

Further information: Do not allow run-off from fire-fighting to enter drains or water courses. Use a water spray to cool fully closed containers.

6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation

Environmental precautions: Do not allow to enter storm sewers/ surface or ground water.

Methods and material for containment and cleaning up: Collect liquid in an appropriate container or absorb with an inert material such as vermiculite, dry sand, or earth; DO NOT use combustible materials. Dispose contaminated material as waste according to item 13. Ensure adequate ventilation..Place in a chemical waste container.

DR-60 Remover Spray Can

7 HANDLING AND STORAGE

Handling Precautions: Keep away from sources of ignition. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid contact with skin and eyes. Avoid breathing vapor or mist. Use only outdoors or in a well-ventilated area or with appropriate respiratory equipment. Do not swallow. When using do not eat, drink or smoke. (See section 8)

Storage Requirements: Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Keep containers upright to prevent leakage. Containers may be hazardous when empty since residue liquid may be present

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Provide adequate ventilation for work and storage areas.

Personal Protective Equipment: Chemical resistant gloves;
Chemical safety glasses;
General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits.
Where concentrations are above recommended limits, use an organic vapor respirator with dust, mist, and fume filters;
Impervious clothing.

Exposure Limits:

CAS NO.	COMPONENT			
	USA OSHA Z-1 (TWA):	500 ppm/2000 mg/m ³		
68476-86-8	Propane/butane	TLV(STEL)	1000 ppm	ACGIH



General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Do not inhale gases / fumes / aerosols. Wash hands before breaks and at the end of work. Avoid contact with eyes and skin.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Colorless liquid that evaporates quickly.		
Physical State:	Liquid in a spray can under pressure	Odor:	Mild
Spec Grav./Density:	0.75 liquid	Solubility:	Negligible
Viscosity:	Kinematic at 37.8 °C (100 °F): 1.2 cSts	Flash Point:	12 °C (54°F) (ASTM D-56), 2-Propanol



DR-60 Remover Spray Can

Boiling Point:	(ASTM D455), liquid 148-176°C (300-350°F), isoalkanes	Vapor Density:	4.5 (Air = 1.0), isoalkanes
Vapor Pressure:	6 mmHg @ 38 °C (100 °F), isoalkanes	Auto-Ignition Temp:	336°C, isoalkanes
pH:	Not determined	UFL/LFL:	No data available
Evaporation Rate:	Not determined		

10

STABILITY AND REACTIVITY

Reactivity:	No dangerous reaction under normal use.
Chemical Stability:	Product is stable under normal conditions.
Conditions to Avoid:	Elevated temperatures, flames
Materials to Avoid:	Strong Oxidizing Agents.
Hazardous Decomposition:	Carbon oxides
Hazardous Polymerization:	Will not occur.

11

TOXICOLOGICAL INFORMATION

Aspiration toxicity : May be fatal if swallowed and enters airways

Skin corrosion/irritation: Irritating to skin.

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP

12

ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Persistency and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

Highly volatile, will partition rapidly to air. Not expected to partition to sediment and wastewater solids.

13

DISPOSAL CONSIDERATIONS

Dispose of in accordance with all applicable local, state and federal regulations

Empty containers may retain product residue (liquid and/or vapor) and can be dangerous.

14

TRANSPORT INFORMATION



DR-60 Remover Spray Can

DOT, IATA, IMDG

UN1950, aerosols, flammable, 2.1

15

REGULATORY INFORMATION

TSCA All components are on the Inventory list

US federal regulations

CERCLA Hazardous Substance List (40 CFR 302.4)

This material does not contain any components with a CERCLA RQ.

SARA 311/312 Hazard classes

- Immediate Hazard - Yes
- Delayed Hazard - No
- Fire Hazard - Yes
- Pressure Hazard - No
- Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 313 (TRI reporting)

Not regulated.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. Clean Water Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. Clean Water Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

Safe Drinking Water Act

Not regulated.


16

OTHER INFORMATION



DR-60 Remover Spray Can

NFPA: Health = 1, Fire = 4, Reactivity = 0, Specific Hazard = n/a



This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Author: Sherwin Inc.

Publication Date: June 14, 2022

Revision No. 0

Revision Date: 6/14/2022