

HM-406 Spray Can

1 PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: HM-406 Spray Can
SDS Number: HM-406 SC
Revision Date: 6/14/2022
Product Use: NDT Inspection Visple Penetrant, Methods A nd C

Supplier Details: Sherwin Inc.
5530 Borwick Avenue
South Gate, CA 90280

Phone: 562-861-6324
Email: sherwin@sherwininc.com
Internet: www.sherwininc.com

Emergency telephone number:

ChemTel 1-800-255-3924 in U.S.A, Canada, Puerto Rico and US Virgin Islands;
ChemTel +1-813-248-0585 outside U.S.A, Canada, Puerto Rico and US Virgin Islands
ChemTel Brazil: 0-800-591-6042, China: 400-120-0751, India: 000-800-100-4086 and Mexico: 01-800-099-0731

2 HAZARDS IDENTIFICATION

Classification of Substance

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Health, Serious Eye Damage/Eye Irritation, 1
Physical, Flammable Aerosols, 1
Health, Skin corrosion/irritation, 2

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: **DANGER**

GHS Hazard Pictograms:



GHS Hazard Statements:

H318 - Causes serious eye damage
H222 - Extremely flammable aerosol
H229 - Pressurized container: may burst if heated
H315 - Causes skin irritation

GHS Precautionary Statements:

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash ... thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P281 - Use personal protective equipment as required.
P301 + P312 - IF SWALLOWED: Call a POISON CENTER/ doctor/...if you feel unwell.
P302 + P352 - IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention.
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P311 - IF exposed or concerned: Call a POISON CENTER/doctor/...
P370 + P378 - In case of fire: Use dry chemical, alcohol resistant foam or dry sand to extinguish.
P403 + P235 - Store in a well-ventilated place. Keep cool.
P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.



HM-406 Spray Can

3 COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Ingredients:		
CAS#	%	Chemical Name:
68476-86-8	40-50%	Propane/ Isobutane
64742-47-8	20-40%	Distillates (petroleum), hydrotreated light
84133-50-6	10-30%	Alcohols, C12-14-secondary, ethoxylated

4 FIRST AID MEASURES

- Inhalation:** Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.
- Skin Contact:** Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor
- Eye Contact:** Immediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids to facilitate irrigation. Get immediate medical attention.
- Ingestion:** Clean mouth with water. Keep respiratory tract clear.
Do NOT induce vomiting or attempt chemical neutralization. If symptoms persist, call a physician.

5 FIRE FIGHTING MEASURES

- Flash Point:** >93°C (>200°F), liquid
- Flash Point Method:** ASTM D-56
- Autoignition Temp:** Not determined
- Lower Explosive Limit:** Propellant: 1.8% (vol.) Gas in air
- UEL:** Propellant: 9.5%(vol.) gas in air
- Suitable extinguishing agents:** Alcohol resistant foam, dry chemical, carbon dioxide
- Special hazards arising from the substance or mixture:** Spray can under pressure. Carbon monoxide and carbon dioxide
- Protective equipment:** Wear self-contained respiratory protective device. Wear fully protective suit
- Unsuitable extinguishing media:** High volume water jet
- Further information:** Do not allow run-off from fire-fighting to enter drains or water courses. Use a water spray to cool fully closed containers.

6 ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures:** Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation
- Environmental precautions:** Do not allow to enter storm sewers/ surface or ground water.
- Methods and material for containment and cleaning up:** Collect liquid in an appropriate container or absorb with an inert material such as vermiculite, dry sand, or earth; DO NOT use combustible materials. Dispose contaminated material as waste according to item 13. Ensure adequate ventilation..Place in a chemical waste container.



HM-406 Spray Can

7	HANDLING AND STORAGE
----------	-----------------------------

Handling Precautions: Keep away from sources of ignition. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid contact with skin and eyes. Avoid breathing vapor or mist. Use only outdoors or in a well-ventilated area or with appropriate respiratory equipment. Do not swallow. When using do not eat, drink or smoke. (See section 8)

Storage Requirements: Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Keep containers upright to prevent leakage. Containers may be hazardous when empty since residue liquid may be present

8	EXPOSURE CONTROLS/PERSONAL PROTECTION
----------	--

Engineering Controls: Provide adequate ventilation for work and storage areas.

Personal Protective Equipment: Chemical resistant gloves;
Chemical safety glasses;
General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits.
Where concentrations are above recommended limits, use an organic vapor respirator with dust, mist, and fume filters;
Impervious clothing.

Exposure Limits:

CAS NO.	COMPONENT	TLV(STEL)	1000 ppm	ACGIH
68476-86-8	Propane/butane	TLV(STEL)	1000 ppm	ACGIH
		TWA	1000ppm	OSHA PEL

Personal Protective Equipment: Chemical resistant gloves;
Chemical safety glasses;
General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits, use an organic vapor respirator with dust, mist, and fume filters;
Impervious clothing



General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Do not inhale gases / fumes / aerosols.
Wash hands before breaks and at the end of work. Avoid contact with eyes and skin.



HM-406 Spray Can

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Yellow Liquid	Odor:	Liquid - Mild
Physical State:	Liquid in a spray can under pressure	Solubility:	Soluble in water
Spec Grav./Density:	Liquid - 0.89	Flash Point:	> 93 °C (> 199 °F) (ASTM D-93), Liquid
Viscosity:	Kinematic at 37.8 °C (100 °F): 7 cSts (ASTM D455), liquid	Vapor Density:	> 1 @ 20 - 25 °C (68 - 77 °F) (Air = 1.0) Liquid
Boiling Point:	240°C (464°F), Liquid	Auto-ignition Temp:	Not determined
Vapor Pressure:	< 0.1 mmHg @ 20 °C (68 °F) Liquid	UFL/LFL:	No data available
pH:	Not determined		
Evaporation Rate:	Not determined		

10 STABILITY AND REACTIVITY

Reactivity:	No dangerous reaction under normal use.
Chemical Stability:	Product is stable under normal conditions.
Conditions to Avoid:	Elevated temperatures
Materials to Avoid:	Strong Acids; Strong Bases Strong Oxidizing Agents.
Hazardous Decomposition:	Carbon oxides, sulphur oxides
Hazardous Polymerization:	Will not occur.

11 TOXICOLOGICAL INFORMATION

Risk of serious damage to eyes.
Irritating to skin.

Acute oral toxicity: LD/50 (Rat) estimated >2000 mg/kg
Acute dermal toxicity: LD/50 (Rabbit) estimated >2000 mg/kg

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC
No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

STOT - single exposure: No data available
STOT - repeated exposure: No data available

12 ECOLOGICAL INFORMATION

Ecotoxicity

84133-50-6 Secondary alcohol ethoxylates : LC50/96h: 3.5 - 4.9 mg/l (Fish)
EC50/48h: 3.1 mg/l (daphnia)

Persistence and degradability

Readily biodegradable.

Bioaccumulative potential

No data available

Mobility in soil

No data available



HM-406 Spray Can

13 DISPOSAL CONSIDERATIONS

Dispose of in accordance with all applicable local, state and federal regulations

Empty containers may retain product residue (liquid and/or vapor) and can be dangerous.

14 TRANSPORT INFORMATION

DOT, IATA, IMDG

UN1950, aerosols,flammable, 2.1

15 REGULATORY INFORMATION

TSCA All components are on the Inventory list

US federal regulations

CERCLA Hazardous Substance List (40 CFR 302.4)

This material does not contain any components with a CERCLA RQ.

SARA 311/312 Hazard classes

Immediate Hazard - Yes

Delayed Hazard - No

Fire Hazard - Yes

Pressure Hazard - No

Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 313 (TRI reporting)

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

California Prop 65

This material does not contain any chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm at concentrations that trigger the warning requirements of California Proposition 65.




HM-406 Spray Can

16

OTHER INFORMATION

NFPA: Health = 2, Fire = 4, Reactivity = 0, Specific Hazard = n/a



This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Author: Sherwin Inc.

Publication Date: June 14, 2022

Revision No. 0

Revision Date: 6/14/2022